


### TECHNICAL DATA

- APPROVALS **CE** **UL**
- CONNECTION TABS 1/4" (0,8X6,3 mm)
- MIN CAPILLARY BENDING RADIUS 5mm
- STAINLESS STEEL CAPILLARY AND BULB
- SETTING TEMPERATURE : 235°C±9°C  
WITH THERMOSTAT AT ROOM TEMPERATURE
- CALIBRATION AND CHECK IN LIQUID BATH
- MIN. TEMPERATURE ON BULB : -10°C
- MAX TEMPERATURE ON BULB : +270°C
- MAX TEMPERATURE ON THE HEAD : +150°C
- INTERNATIONAL PROTECTION : IP00

### ELECTRIC DIAGRAM



120/240 VAC, 20 A - UL, C.S.A.

THERMOSTAT TU V RM T.F. 235°C COMTHERM



**c.a.e.m.**  
THERMOSTAT AND SENSOR

Via Rivera 106-108  
10040 ALMESE (TO) ITALY

SCALA :

DATA : 21-10-2015

DIS. TACCA GIANLUCA

FORMATO: A4

SOSTITUISCE IL:

DIS. N°

LP6231

MATERIALE

FINITURA

A TERMINI DI LEGGE CI RISERVIAMO LA PROPRIETA' DEL PRESENTE DISEGNO CON DIVIETO DI USO E RIPRODUZIONE  
UNDER THE TERMS OF LAWS WE RESERVE THE PROPERTY OF THIS DRAWING WITH PROHIBITION OF USE AND DUPLICATION